

# surfaceform

## Travertino Data Sheet

### **Recommended Use:**

For high quality decoration in commercial and domestic buildings.  
Suitable for interior and some exterior applications

### **Ingredients**

Aged finely filtered slaked lime putty  
Special marble powders  
Water and acrylic binder (less than 3% total in wet volume).

### **Physical characteristic**

Has a directional random open texture contrasting against a smooth closed texture  
The finish has is matt  
Ready to use white plaster  
Naturally anti mould and mildew  
Very high adhesion to substrates.

### **Colour**

Endless variety of colours and options available, consult with Surfaceform for samples.

### **Fire, Smoke & Explosive hazards**

Fire Growth Rate Index-04: Class O British and Class B Euroclass  
Smoke Growth Rate Index: Class O British and Class B Euroclass  
Non combustible material.  
Tests carried out in accordance with BSEN 13823:2002

### **VOC:**

0g voc per litre in white colour.  
20g voc per litre if coloured using our colour additives.

### **Skin absorption**

Skin protection is recommended as lime products are naturally caustic. In the case of contact with skin rinse thoroughly with soap and water.  
Keep out of the reach of children

#### **Head Office**

A19 Kilcronagh Business Park  
Cookstown  
Northern Ireland. BT80 9HG  
T +44 (0)28 8676 9607

#### **London Office**

2nd Floor  
145-157 St John Street  
London. EC1V 4PY  
T 0845 519 4076

#### **Email**

info@surfaceform.com

#### **Website**

[www.surfaceform.com](http://www.surfaceform.com)

**Eye absorption**

Avoid contact with eyes at all times as lime products are caustic and may cause irritation. In the event of contact with eyes, rinse thoroughly with water and seek medical attention.

Eye protection must be worn.

**Inhalation:**

A wet material with no odour or dust. Remove victim to fresh air if any unusual symptoms occur.

Masks are recommended

**Ingestion**

Products are not suitable for human consumption. Seek medical advice if consumed.

**Packaging**

24kg Plastic containers

8kg Plastic containers

**Disposal**

Plaster must be disposed of according to local regulations.

Containers must be recycled or reused.

**Storage**

Protect from frost storing upright in temperatures between 5 to 30 degrees C.

**Mixing**

Water on the surface is normal and should be removed before mixing. If a colour is required mix the plaster firstly, then add the colour and mix until a continuous shade is achieved. All lime based products lose viscosity when shaken and need to sit for 12 to 24 hours after mixing to regain their density.

**Coverage**

2-9 kg per meter sq

**Drying Time**

Touch dry – 3hours at 20 C

Carbonation - 48hours at 20 C

Fully dry – 180 days.

**Head Office**

A19 Kilcronagh Business Park  
Cookstown  
Northern Ireland. BT80 9HG  
T +44 (0)28 8676 9607

**London Office**

2nd Floor  
145-157 St John Street  
London. EC1V 4PY  
T 0845 519 4076

**Email**

info@surfaceform.com

**Website**

[www.surfaceform.com](http://www.surfaceform.com)

**Application**

Applied onsite in multiple layers by hand using tools such as metallic trowels, plastic trowels and spatulas.

**Thickness**

1.5-2.5mm in 3 coats

**Substrate**

Can be used on most internal and external substrates. Please refer to our substrate advice documents for full substrate details

**Shelf Life**

2 years in an unopened container

*This document was created as a general guide for using Surfaceform to complete projects and to help with specifications. This is a general overview and offers no guarantee for any problems that may arise. Surfaceform or its employees will not be responsible or liable for any claim or action taken against them in relation to advice offered by this document.*

**Head Office**

A19 Kilcronagh Business Park  
Cookstown  
Northern Ireland. BT80 9HG  
T +44 (0)28 8676 9607

**London Office**

2nd Floor  
145-157 St John Street  
London. EC1V 4PY  
T 0845 519 4076

**Email**

[info@surfaceform.com](mailto:info@surfaceform.com)

**Website**

[www.surfaceform.com](http://www.surfaceform.com)