

Relief - Suitable for application to interior walls and ceilings

Product	
Optional Reinforcing System *Reinforcing System : recommend the use of our reinforcing system to reduce the risk of cracks appearing on the surface. The system will not stop substrate cracks.	Included <input type="checkbox"/> Excluded <input type="checkbox"/>
Manufacturer	Surfaceform A19 Kilcronagh Business Park, Cookstown, Co. Tyrone BT80 9HJ
Installer	Supplied and installed by Surfaceform
Manufacturer Email	info@surfaceform.com
Manufacturer Tel	0208 816 8160 or 028 867 69607
Product Location	
Drawing Numbers	
Thickness	As per Design
Substrate	Please see substrate guideline documents for detailed information as below:
Lead Time	6-8 weeks from order to allow for batching and batch sample approval
installation	The panels are attached to the substrate (or metallic sub frame) with adhesive and mechanical fixing. Curved areas are possible for most of our designs at an extra cost. Site templates will be required. Areas with great temperature variations are not suitable. Areas greater than 35msq or 9M in length will need an expansion joint designed into the finish. Larger walls are prone to small hairline cracks appearing on the surface due to substrate movements.

Programme	Finish is installed on site as late in the build as possible and may need to be protected during the completion of the project. Prior TBC at Order stage.
Optional Imprinted detail	A sized EPS or PDF is provided to Surfaceform of the finalised design.
Drying	Drying times will vary due to site conditions. Min 10°C – max30°C for storage and application
Finish	The Surface can be decorated for a seamless look

Fire	The Surfaceform relief product is non-combustible providing no contribution to fire in accordance with EN 13501-1
-------------	---

Substrate

Please see below for substrate guidelines.

Substrate Construction Guidelines

Substrate is critical to achieve a good finish and should allow for the product to be well aligned when fixed. It is important that a solid flat surface with no bumps or hollows is provided for fitting. Any internal or external corners must be plumb to allow for a straight alignment of the panels and to achieve a true and straight corner.

We recommend a MF substrate is created with uprights at 300mm centers. Walls need to be constructed plum and straight with plenty of horizontal supports. The supports need to be constructed to support all 4 sides of the boards. 12mm plywood is to be attached to the MF frame by screws. Foil backed 12.5mm Plasterboard (foil towards the ply) must be then fixed to the ply using screws. Joints should be staggered between the plywood and plasterboard. Foil backed board is required as this reduces the chances of the moisture in the adhesive seeping into the ply causing it to swell, which may result in cracking of joints. Alternatively the ply can be sealed 24 hours before application of standard plasterboard.

The aim is to achieve a very well constructed solid straight and plumb wall with no bumps, ridges between sheets or structure movements. Tolerances should be no more than +/- 1.5mm in 1000mm.

Please check with the MF supplier that it can support the weight of the selected Surfaceform Relief design – substrate requirements will vary depending on designs and scale of the project. If the substrate is not allowing for typical installation, the Surfaceform Relief products may be fixed on a metallic sub frame with plaster bandages.

Please Check substrate confirmation with Surfaceform prior to building as certain designs may affect the requirements.

This document was created as a general guide for Surfaceform products and to help with specifications. This is a general overview and offers no guarantee for any problems that may arise. Surfaceform or its employees will not be responsible or liable for any claim or action taken against them in relation to advice offered by this document